

# RAUCKMAN SILICONE CONDUCTOR COVER SELECTOR CHART

	CONDUCTOR DIAMETER IN INCHES																																									
	0.10	0.15	0.20	0.25	0.30	0.35	0.40	0.45	0.50	0.55	0.60	0.65	0.70	0.75	0.80	0.85	0.90	0.95	1.00	1.05	1.10	1.15	1.20	1.25	1.30	1.35	1.40	1.45	1.50	1.55	1.60	1.65	1.70	1.75	1.80	1.85	1.90					
COPPERWELD			3 #12	8A	6A	4A	3 #6	2A	1/0F	2/0F	1N	3/0F	2/0K	3/0F	4/0F	4/0E	250EK	250E	300EK	300E	350EK	350E																				
ACSR* / ACSS*			8	6	5	4	3	2	1	1/0	2/0	3/0	4/0	250	300	350	400	450	500	550	600	650	700	750	800	900	1000															
COPPER STRAND	10	8	7	6	5	4	3	2	1	1/0	2/0	3/0	4/0	250	300	350	400	450	500	550	600	650	700	750	800	900	1000															
COPPER SOLID	10	8	7	6	5	4	3	2	1	1/0	2/0	3/0	4/0																													
RCC-040	█																																									
RCC-075																																										
RCC-100																																										
RCC-175																																										

\*Some ACSR and ACSS conductor sizes are listed more than once in this chart since the stranding design can affect the conductor’s overall outside diameter. For example; 795 MCM is available in different stranding configurations such as; Coot, Drake, Condor, Cuckoo, Tern and Mallard. Coot is the smallest diameter at 1.04” and Mallard’s outside diameter of 1.14” is the largest. If a conductor size (MCM) is available in more than one outside diameter the minimum and maximum diameters are shown in the chart above.

© Copyright 2016 Rauckman Utility Products, LLC.

Rauckman Utility Products, LLC.

33 Empire Drive

Belleville, IL 62220

phone: 618-234-0001

fax: 618-234-0003

[www.rauckmanutility.com](http://www.rauckmanutility.com)

